



## CowboyStudio Continuous Lighting Kit Setup Instructions

This document contains step-by-step instructions for setting up one of our continuous lighting kits. Your kit should include:

- One (1) light stand
- One (1) soft white umbrella
- One (1) ac light socket
- One (1) compact fluorescent light bulb

The exact contents of your kit may vary based upon your order. Refer to Figure 1 for the items included in the instructional kit.



Step 1: Remove the protective cap from the top of the light stand as shown in Figure 2.

Step 2: Loosen the wing nut at the top of the light stand legs by turning counterclockwise as shown in Figure 3. Expand the legs so that the light stand will stand up on its own, and then tighten the wing nut.

Step 3: Open the flip locks on the light stand joints to allow the light stand sections to move freely. Raise and lower the sections of the stand to the desired height, and close the flip locks to hold the sections in place. Refer to Figure 4 for a detailed look at these locks.

At this point, the light should stand on its own at your desired height, as illustrated in Figure 5.





Figure 6



Figure 7

Step 4: Screw the light bulb into the ac light socket. Make sure to use the base when tightening, not the top, as shown in Figure 6. When done, your light bulb and ac light socket should match Figure 7.




Figure 8



Figure 9

Step 5: Mount the ac light socket on the light stand. Start by loosening the screw at the base of the ac light socket. Slide the ac light socket onto the tip of the light stand and tighten the screw until the ac light socket fits securely as shown in Figure 8. Your assembly should then look like Figure 9.




Figure 10

Step 6: Open the umbrella and insert the stem of the umbrella into the umbrella hole in the ac light socket until the umbrella is secure as shown in Figure 10.

Once fully assembled, your continuous lighting kit should match that in Figure 11. To use, plug in the cord on the ac light socket and flip the power switch.



Figure 11